

FIREXO 6L ALL FIRES EXTINGUISHER

PRODUCT	FIREXO 6L ALL FIRES
MODEL/PRODUCT NO.	809-765-347-876
CAPACITY	6 LITRES
OVERALL PRODUCT HEIGHT	520 mm
CYLINDER HEIGHT	430 mm
CYLINDER DIAMETER	162 mm
CYLINDER MATERIAL	STEEL
PRESSURISING GAS	NITROGEN
TEST PRESSURE	30 BAR
WORKING PRESSURE	12 BAR
WEIGHT (FULL)	10.45 KG*
WEIGHT (EMPTY)	3.65 KG
SPRAY RANGE	1-4 m
DISCHARGE TIME	25-35 seconds
TEMPERATURE RANGE	-15 °C / +60 °C
WARRANTY	5 YEARS
FIRE RATINGS	34A/113B/C/D/ELECTRICAL/75F/LITHIUM-ION



METHOD OF USE

In the event of a fire hold extinguisher upright, pull out safety pin, point hose at base of fire, squeeze handle and sweep side to side.

Discharge entire contents onto the fire from a 1m-3m distance.

Store upright and away from direct sunlight or heat source.

Protect from frost.

Replace or recharge after use.

Tested on electrical equipment fires to 35kV.

*5% +/- tolerance variance in accordance with EN3-7

© FIREXO 2024

This data specification sheet provides guidance only. It does not represent scientific or professional advice to any recipient or third party reader. Whilst great care has been taken to compile accurate data herein, FIREXO does not accept any responsibility or legal liability for any errors or omissions.